

GOOD ENERGY PVC

KPA CENTER PIVOT PVC ROOF WINDOW



VARIANT	1500
PANE	
Construction	4-12-3HS-12-3H
34 mm triple glazing	✓
Low E	✓✓
Gas	Argon
Toughened	✓
U_g (W/m ² K)	0.77
Total solar energy transmittance	0.55
WINDOW	
U_w (W/m ² K)	1.1
Water tightness	E1500
Air permeability	Class 3
Resistance to wind load	Class C3*
Sound reduction	33 [-1,-3] dB
COLOUR	
White	✓

* M8A, M10A, P8A: no performance data



NEXT 20
GUARANTEE



EASY CLEAN
PVC



MAX PROTECT



THERMOSTAT



ENERGY +

APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Centre pivot
- Extra sliding gasket
- ENERGY+ - Triple glazing
- THERMOSTAT - Extra heat reflecting coating
- Toughened outer glass
- Two passive ventilation positions via handle
- 20 years guarantee
- Easy installation

MATERIAL

- EASY-CLEAN PVC - Lead free PVC
- Polystyrene insulation insertion
- Steel reinforcement

COVER PARTS

- Aluminium, lacquered, RAL 7043

HANDLE

- New, ergonomically designed moulded zinc handle, lacquered

HINGE

- Centre pivot



TECHNICAL DATA

MEASURES [cm]								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	EFFECTIVE LIGHT AREA m ²
KPA C2A	55x78	55	77,8	39,8	64,9	37,3	59	0.220
KPA C4A	55x98	55	97,8	39,8	84,9	37,3	79	0.295
KPA C6A	55x118	55	117,8	39,8	104,9	37,3	99	0.369
KPA F4A	66x98	66	97,8	50,8	84,9	48,3	79	0.382
KPA F6A	66x118	66	117,8	50,8	104,9	48,3	99	0.478
KPA M4A	78x98	78	97,8	62,8	84,9	60,3	79	0.476
KPA M6A	78x118	78	117,8	62,8	104,9	60,3	99	0.597
KPA M8A	78x140	78	139,8	62,8	126,9	60,3	121	0.729
KPA M10A	78x160	78	160	62,8	146,9	60,3	141	0.850
KPA P6A	94x118	94,2	117,8	78,8	104,9	76,3	99	0.755
KPA P8A	94x140	94,2	139,8	78,8	126,9	76,3	121	0.925
KPA S6A	114x118	114	117,8	98,8	104,9	96,3	99	0.953
KPA U4A	134x98	134	97,8	118,8	84,9	116,3	79	0.919

FLASHING COMPATIBILITY TABLE (ACCORDING TO PROFILE HEIGHT OF ROOFING MATERIAL)								
SIZE CODE	Slate with soakers 0-16mm (2x8mm)	Slate with one-piece side element 0-16 mm (2x8 mm)	Tile (16-50mm)	Interlocking flat tile (16-50mm)	Universal (16-120mm)	Standing seam	Plain tile	Flush flashing 0-16mm (2x8mm)
KPA C2A	KSF C2A	KLS C2A	KTF C2A	KFT C2A	KUF C2A	KSS C2A	KFP C2A	KFF C2A
KPA C4A	KSF C4A	KLS C4A	KTF C4A	KFT C4A	KUF C4A	KSS C4A	KFP C4A	KFF C4A
KPA C6A	KSF C6A	KLS C6A	KTF C6A	KFT C6A	-	-	-	-
KPA F4A	KSF F4A	KLS F4A	KTF F4A	KFT F4A	KUF F4A	-	KFP F4A	KFF F4A
KPA F6A	KSF F6A	KLS F6A	KTF F6A	KFT F6A	KUF F6A	KSS F6A	KFP F6A	KFF F6A
KPA M4A	KSF M4A	KLS M4A	KTF M4A	KFT M4A	KUF M4A	KSS M4A	KFP M4A	KFF M4A
KPA M6A	KSF M6A	KLS M6A	KTF M6A	KFT M6A	KUF M6A	KSS M6A	KFP M6A	KFF M6A
KPA M8A	KSF M8A	KLS M8A	KTF M8A	KFT M8A	KUF M8A	KSS M8A	KFP M8A	KFF M8A
KPA M10A	KSF M10A	KLS M10A	KTF M10A	KFT M10A	KUF M10A	KSS M10A	KFP M10A	KFF M10A
KPA P6A	KSF P6A	KLS P6A	KTF P6A	KFT P6A	KUF P6A	KSS P6A	KFP P6A	KFF P6A
KPA P8A	KSF P8A	KLS P8A	KTF P8A	KFT P8A	KUF P8A	KSS P8A	-	-
KPA S6A	KSF S6A	KLS S6A	KTF S6A	KFT S6A	KUF S6A	KSS S6A	KFP S6A	KFF S6A
KPA U4A	KSF U4A	KLS U4A	KTF U4A	KFT U4A	KUF U4A	-	KFP U4A	KFF U4A

For Combi flashing compatibility please visit www.dakea.co.uk

BLIND COMPATIBILITY TABLE						
SIZE CODE	BLACKOUT	ROLLER	VENETIAN	ANTI-HEAT	SOLAR ROLLER SHUTTER	
KPA C2A	DUA C2A	RHA CXA	PAA C2A	MIA CXA	SSR C2A	
KPA C4A	DUA C4A	RHA CXA	PAA C4A	MIA CXA	SSR C4A	
KPA C6A	-	-	-	MIA CXA	SSR C6A	
KPA F4A	DUA F4A	RHA FXA	PAA F4A	MIA FXA	SSR F4A	
KPA F6A	DUA F6A	RHA FXA	PAA F6A	MIA FXA	SSR F6A	
KPA M4A	DUA M4A	RHA MXA	PAA M4A	MIA MXA	SSR M4A	
KPA M6A	DUA M6A	RHA MXA	PAA M6A	MIA MXA	SSR M6A	
KPA M8A	DUA M8A	RHA MXA	PAA M8A	MIA MXA	SSR M8A	
KPA M10A	DUA M10A	RHA MXA	PAA M10A	MIA MXA	SSR M10A	
KPA P6A	DUA P6A	RHA PXA	PAA P6A	MIA PXA	SSR P6A	
KPA P8A	-	-	-	MIA PXA	SSR P8A	
KPA S6A	DUA S6A	RHA SXA	PAA S6A	MIA SXA	SSR S6A	
KPA U4A	DUA U4A	RHA UXA	PAA U4A	MIA UXA	SSR U4A	

PANE 15
Triple pane, heat reflecting and energy saving insulated glass
4-12-3HS-12-3H

U_g: 0,77 W/m²K
U_w: 1,1 W/m²K

4 mm float glass Low-E coating [reflects heat] Stainless steel [warm edge] spacer 3 mm heat strengthened glass Low-E coating [reflects heat] Stainless steel [warm edge] spacer 3 mm toughened safety glass

AVAILABLE SIZES [cm]

C2A	C4A	C6A	F4A	F6A	M4A	M6A	M8A	M10A	P6A	P8A	S6A	U4A
55x78	55x98	55x118	66x98	66x118	78x98	78x118	78x140	78x160	94x118	94x140	114x118	134x98

www.dakea.com

CE²¹
EN 14351-1: 2006
+A2: 2016

